



## WELL LIGHT

**15702BZ-LMA30K**

VARIABLE OUTPUT LED 3000K FLAT TOP

| DETAILS   |            |
|-----------|------------|
| FINISH:   | Bronze     |
| MATERIAL: | Aluminum   |
| GLASS:    | Clear Lens |
| DIMMABLE: | No         |

| DIMENSIONS |       |
|------------|-------|
| WIDTH:     | 4.5"  |
| HEIGHT:    | 4"    |
| DEPTH:     | 4.5   |
| WEIGHT:    | 3.4lb |

| LIGHT SOURCE              |                                        |
|---------------------------|----------------------------------------|
| LIGHT SOURCE:             | LumaCore                               |
| LED NAME:                 | 30G4SE-12W                             |
| WATTAGE:                  | 12w, 8w, 5w, 3w LumaCore LED *Included |
| VOLTAGE:                  | 12v                                    |
| VOLT AMPS:                | 12.4, 7.8, 5.3, 3.2                    |
| LUMENS:                   | 750, 475, 350, 260                     |
| CRI:                      | 80                                     |
| INCANDESCENT EQUIVALENCY: | 1 x 60w, 45w, 35w, 25w                 |
| DIMMABLE:                 | No                                     |
| TRANSFORMER REQUIRED:     | Yes                                    |

| MOUNTING   |         |
|------------|---------|
| LEAD WIRE: | 1 X 36" |

| SHIPPING       |      |
|----------------|------|
| CARTON LENGTH: | 7    |
| CARTON WIDTH:  | 7    |
| CARTON HEIGHT: | 13.5 |
| CARTON WEIGHT: | 4.5  |

### PRODUCT DETAILS:

- LumaCore Series products carry a lifetime limited warranty
- PVC constructed concrete pour kit and burial sleeve are supplied
- Incorporates CREE LEDs with application performance tested by CREE
- Wet Rated; Suitable for outdoor settings
- Wattage settings include: 3W (260 Lumens), 5W (350 Lumens), 8W (475 Lumens), 12W (750 Lumens)
- Includes a dense foam cap to prevent concrete from entering
- Photometrics based off engine photometrics
- Optimal drive-over protection up to 4,500 lbs

# HINKLEY

**HINKLEY**  
33000 Pin Oak Parkway  
Avon Lake, OH 44012

**PHONE: (440) 653-5500**  
Toll Free: 1 (800) 446-5539

[hinkley.com](http://hinkley.com)